

STRIKER ACH

ADVANCED COMBAT HELMET LEVEL IIIA STANDARD CUT



SPECIFICATIONS

- + **Protection:** Level IIIA including frag protection
- + **NIJ Standard 0106.01 TESTED:** This product has been independently tested by an NVLAP accredited NIJ approved laboratory to meet or exceed ballistic resistance as specified under NIJ Standard 0106.01
- + **MIL-STD-662F:** This product has been independently tested by an NVLAP accredited NIJ approved laboratory against frag resistance as specified under MIL-STD-662F
- + **Materials:** Hybridized Kevlar® fibers and UHMWPE Spectra® shell construction
- + **Head Protection:** Front, back, crown, and top of the head
- + **Weight Tolerance:** +/- .15 lbs / .068 kg
- + **Adjustable Harness:** Multiple harness options and comes standard with 4 pt harness
- + **Padding:** D3O® TRUST Stealth™ 7-pad system
- + **Sizing:** Circumference is measured around the head, similar to hat sizing. All sizes are measured in inches. If a measurement falls on a dividing line between sizes, select the larger of the two sizes to ensure maximum ballistic protection.
- + **Warranty:** 5 years on all ballistic material excluding exterior cover, 1 year on exterior cover material and workmanship

COLORS



SIZE & WEIGHT CHART

SIZE	LENGTH	WIDTH	CIRCUMFERENCE	WEIGHT		
S	7.1" to 7.6"	5.6" to 6.0"	21.1" to 21.9"	1220 g	1.2 kg	2.7 lbs
M	7.6" to 7.9"	6.0" to 6.3"	21.9" to 22.7"	1280 g	1.3 kg	2.8 lbs
L	7.9" to 8.3"	6.3" to 6.5"	22.7" to 24"	1350 g	1.4 kg	3.0 lbs
XL	8.3" to 8.8"	6.5" to 7.1"	24" to 26"	1450 g	1.5 kg	3.2 lbs

NIJ 0106.01 HANDGUN THREATS

PROJECTILE	GR	VEL FT/S	VEL M/S	[+/- FT/S]	[+/- M/S]
.357 Magnum Jacketed Soft Point (JSP)	158	1395	425	(+/- 50)	(+/- 15)
9mm Full Metal Jacketed Round Nose (FMJ RN)	124	1400	427	(+/- 30)	(+/- 9)
.44 Magnum Semi Jacketed Hollow Point (SJHP)	240	1400	427	(+/- 30)	(+/- 9)

MIL-STD-662F FRAG THREATS

PROJECTILE	GR	VEL FT/S	VEL M/S	V50 FT/S	V50 M/S
US MIL-STD Frag 2 gr. RCC	2	4200	1280	4415	1346
US MIL-STD Frag 4 gr. RCC	4	3475	1059	3211	979
US MIL-STD Frag 16 gr. RCC	16	2475	754	2346	715
US MIL-STD Frag 64 gr. RCC	64	1750	533	1755	535
US MIL-STD Frag 17 gr. FSP	17	2200	671	2221	677

HIGHCOMARMOR.COM



MIL-STD 662F



NIJ 0106.01 TESTED



MULTI HIT



LIGHTWEIGHT